



Legend

COMMON PATH OF TRAVEL
Provided
Max Allowed

TRAVEL DISTANCE
Provided
Max Allowed

EXIT NUMBER
ACTUAL # OF OCCUPANTS
EXITING AT THIS LOCATION
MAXIMUM CAPACITY TO EXIT

WALL MOUNTED EXIT SIGN,
(E DENOTES EXISTING)
SEE ELECTRICAL DRAWINGS

CEILING MOUNTED EXIT SIGN,
(E DENOTES EXISTING)
SEE ELECTRICAL DRAWINGS

FIRE EXTINGUISHER
FEC

FIRE EXTINGUISHER CABINET.
FIRE EXTINGUISHER CABINET NOT TO PROJECT
MORE THAN 4-INCHES FROM FINISHED WALL
INTO THE CIRCULATION PATH

ITEMS DENOTED WITH AN "E" ARE EXISTING TO REMAIN U.N.O.
ITEMS DENOTED WITH AN "R" ARE RELOCATED U.N.O.

Life Safety Notes

ALLOWED:

TRAVEL DISTANCE:	
B: BUSINESS	300'-0"
F-1: FACTORY	400'-0"
S-1: STORAGE	400'-0"
COMMON PATH OF TRAVEL:	
B: BUSINESS	100'-0"
F-1: FACTORY	100'-0"
S-1: STORAGE	100'-0"
DEAD END CORRIDOR:	
B: BUSINESS	50'-0"
F-1: FACTORY	50'-0"
S-1: STORAGE	50'-0"

1. THIS BUILDING IS EQUIPPED WITH A SPRINKLER SYSTEM
SEE FIRE SPRINKLER DRAWINGS FOR EXACT DETAILS.
2. THIS BUILDING IS EQUIPPED WITH A FIRE ALARM SYSTEM
TO MONITOR THE SPRINKLER SYSTEM.

I Ground Floor Life Safety Plan
LS1.0 Scale: 3/32" = 1'-0"