

TGFU.R25992 - Roofing Systems

Note: We are enhancing our systems and you may notice duplicate entries/missing/outdated data. During this interim period, please contact our Customer Service at <https://www.ul.com/about/locations>

Roofing Systems

R25992

Polyglass USA Inc
 1111 W Newport Center Dr
 Deerfield Beach, FL 33442 United States

OTHER SYSTEMS

Class A

1. Deleted

2. Deck: NC

Incline: Unlimited

Insulation: — Any UL Classified polyisocyanurate, any thickness.

Base Sheet: — One ply "Polystick MTS", "Polystick MTS Plus", "Polystick MU-X", "Polystick XFR", "Polystick® IR-Xe", or "PolyVap SA G" self-adhered or "Elastobase V" or "PolyAnchor UDL 40" mechanically fastened.

Surfacing: — Any UL Listed or Classified copper panels or UL Listed or Classified steel standing seam panels, stone coated shingles, 26 gauge minimum.

3. Deck: C-15/32 or spaced sheathing

Incline: Unlimited

Impact: 4

Base Sheet (optional): — Minimum one ply Type 15 or Type 30 asphalt saturated felt or Type G1 or Type G2 asphalt saturated glass mat, or "Elastobase V" or "PolyAnchor UDL 40" mechanically fastened, or "Polystick XFR", "Polystick MTS", "Polystick MTS Plus", "Polystick MU-X", "Polystick® IR-Xe", or "PolyVap SA G" self-adhered.

Underlayment: — One ply "Polystick XFR" self-adhered.

Insulation (optional): — "Polytherm" or "Polytherm-H" or any UL Classified polyisocyanurate, perlite, wood fiber or polyisocyanurate/perlite board, any thickness mechanically fastened or adhered with any UL Classified insulation adhesive.

Ply Sheet (optional): — Minimum one ply Type 15 or Type 30 asphalt saturated felt or Type G1 or Type G2 asphalt saturated glass mat or "Elastobase V" or "PolyAnchor UDL 40" mechanically fastened or "Polystick XFR", "Polystick MTS", "Polystick MTS Plus", "Polystick MU-X", "Polystick® IR-Xe", or "PolyVap SA G" self-adhered.

Surfacing: — Any UL Listed or Classified copper panels or UL Listed or Classified steel standing seam panels, stone coated shingles, 26 gauge minimum.

4. Deck: C-15/32 or spaced sheathing

Incline: Unlimited

Base Sheet (optional): — Minimum one ply Type 15 or Type 30 asphalt saturated felt or Type G1 or Type G2 asphalt saturated glass mat, or "Elastobase V" or "PolyAnchor UDL 40" mechanically fastened or "Polystick MTS", "Polystick MTS Plus", "Polystick MU-X", "Polystick® IR-Xe", or "PolyVap SA G" self-adhered.

Underlayment: — Two plies "Polystick XFR" self-adhered.

Insulation (optional): — "Polytherm" or "Polytherm-H" or any UL Classified polyisocyanurate, perlite, wood fiber or polyisocyanurate/perlite board, any thickness mechanically fastened or adhered with any UL Classified insulation adhesive.

Feedback

Ply Sheet (optional): — Minimum one ply Type 15 or Type 30 asphalt saturated felt or Type G1 or Type G2 asphalt saturated glass mat or "Elastobase V" or "PolyAnchor UDL 40" mechanically fastened or "Polystick XFR", "Polystick MTS", "Polystick MTS Plus", "Polystick MU-X", "Polystick® IR-Xe", or "PolyVap SA G" self-adhered.

Surfacing: — Any UL Classified minimum 0.032 inches thick aluminum panels, mechanically fastened.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."